

INTERIOR RADIATION CONTROL COATING SYSTEMS FOR ENERGY CONSERVATION & COMFORT CONTROL



1 COMPONENT SYSTEM

5.0 US GALLONS (18.925L)

**COVERAGE: 2,000 SQFT/BUCKET
SPRAY-APPLIED**

OPTICAL PROPERTIES:

E = 0.170-0.190

R = 82-86%

SUBSTRATE DEPENDENT

SOLVENT: DI WATER

BINDER: SILICONIZED ACRYLIC

OPERATIONAL TEMP:

-100F TO +400F

STORAGE TEMP:

+40F TO +80F

VOC:

218.10 REG

52.98 ACT

VISCOSITY:

2-4 cP

SHELF LIFE:

1 YEAR

CURE TIME:

FAST

FIRE RATING: UNDETERMINED

FLAME: N/A

SMOKE: N/A

NON-CONDUCTIVE

MOISTURE PERMEABLE

MOLD RESISTANT

1 COMPONENT SYSTEM

5.0 US GALLONS (18.925L)

**COVERAGE: 2,000 SQFT/BUCKET
SPRAY-APPLIED**

OPTICAL PROPERTIES:

E = 0.145-0.170

R = 84-87%

SUBSTRATE DEPENDENT

SOLVENT: DI WATER

BINDER: 100% SILICONE EMULSION

OPERATIONAL TEMP:

-100F TO +1,000F

STORAGE TEMP:

+40F TO +80F

VOC:

215.48 REG

53.55 ACT

VISCOSITY:

2-4 cP

SHELF LIFE:

1 YEAR

CURE TIME:

SLOW

FIRE RATING: CLASS A

FLAME: 0.0

SMOKE: 0.0

NON-CONDUCTIVE

MOISTURE PERMEABLE

MOLD RESISTANT

RIMA-I VERIFIED